



PT

14

(TRA CODE:L-2)POWER TRACTION

For earthmovers, graders, loaders and industrial tractors. The directional lugs produce self-cleaning action and provide excellent traction on loose and soft soil and sand.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		G/@40km/h		L/ @10km/h	
							mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa
WIDE BASE TIRE														
15.5-25	12	—	△	23.5	0.94	12.00/1.3	410	16.14	1286	50.63	2650	250	5600	400
17.5-25	12	—	△	26.5	1.05	14.00/1.5	464	18.25	1366	53.78	2900	200	6150	350
	16	—	△								3350	275	7300	475
20.5-25	12	—	△	27.0	1.07	17.00/2.0	539	21.33	1502	59.13	3550	175	6700	250
	16	—	△								4000	225	8250	350

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

