



RSEHT 39

(TRA CODE:L-5) ROCK SERVICE
EXTRA HIGH TREAD

Premium deep tread specially designed for loaders, 250% deeper tread than E-3/L-3. Its wide tread and gear-type lug design combined with cut resistant tread compound produce superior resistance to cut, wear and tear and offer riding stability without losing any traction capability. Suited for more severe working conditions, such as: power construction, open-pit mine, quarry, construction. Longer life than regular L-3 and L-4 tires and less downtime from more frequent tire changing.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
WIDE BASE TIRE												
20.5-25	16	△	△	71.0	2.80	17.00/2.0	524	20.64	1552	61.12	8250	350
	20	△	△								9500	450
	24	—	△								10300	525
23.5-25	16	△	—	78.5	3.10	19.50/2.5	600	23.63	1676	66.00	9500	300
	20	△	△								10900	375
	24	△	—								12500	475

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
65 SERIES LOW PROFILE TIRE												
35/65-33	24	—	△	95.0	3.75	28.00/3.5	855	33.67	2108	83.00	19000	350
	30	—	△								21800	450
	32	—	△								22400	475
	36	—	△								23600	525
	42	—	△								25750	600

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

