



**RSS**

**27**

**(TRA CODE:E-4) ROCK STAR SUPREME E-4**

Designed for mining dump trucks. Heavy-duty nylon carcass and tenacious tread compounding provide excellent service of tires in mining, constructions and water conservancy project. Extra deep tread gives good wear resistance and longer tire life.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Transportation @50km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
18.00-33	32	—	△	56.0	2.20	13.00/2.5	498	19.6	1877	73.9	10000	575
	36	—	△								10600	625
21.00-33	32	△	—	43.0	1.69	15.00/3.0	575	22.6	1953	76.9	10300	500
21.00-35	32	—	△	53.5	2.12	15.00/3.0	572	22.5	2052	80.78	12150	500
	36	—	△								12850	550
	40	—	△								13500	600
	42	—	△								13800	625
24.00-35	42	—	△	57.0	2.25	17.00/3.5	653	25.7	2175	85.64	17000	575
	48	—	△								18500	650
27.00-49	42	—	△	73.0	2.87	19.50/4.0	737	29.0	2702	106.4	23000	500
	48	—	△								25000	575
33.00-51	50	—	△	75.0	2.95	24.00/5.0	894	35.2	3061	120.5	33500	500
	58	—	△								35500	575
37.00-57	60	—	△	80.0	3.15	27.00/6.0	1016	40.0	3438	135.35	46250	525
	68	—	△								50000	600
40.00-57	60	—	△	75.0	2.95	29.00/6.0	1097	43.2	3594	141.48	50000	475
	68	—	△								54500	550

**BRISBANE**

28 Ashover Rd  
Rocklea  
QLD 4106

**MELBOURNE**

41 Paraweena Dr  
Truganina  
VIC 3029

**SYDNEY**

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

**PERTH**

8 Glassford Rd  
Kewdale  
WA 6105

