

freedomtyres.com.au








RUNFLAT YU63











RFT Product Features:

- 1. No more delays or being stranded on remote highways due to a flat tire. RFT products will continue to drive at up to 80 KPH without having to be replaced immediately.
- 2. Helps to avoid accidents caused by the loss of control from punctures or air leaks, increasing
- 3. Even when the tire begins leaking air you can drive to your local tire dealer to have it repaired. RFT technology also means there is no need to carry a spare which helps increase storage space within the vehicle.

Run-flat tires (RFT), also known as "self-supporting run-flat tires," are an important safety feature for any vehicle. A Run-flat tire is built with a thicker sidewall to help support the tire shape after losing air. This allows the tire to continue to run safely, but at a limited speed and mileage. When normal tires are punctured, they can instantly lead to a severe sidewall collapse; in the event of a collapse, the vehicle loses its only support which can cause the vehicle's center of gravity to change instantaneously. RFT helps to lessen the severity of a flat tire and allows you to get to the closest destination safely.

GALLOPRO RUNFLAT YU63

| RIM | SIZE | LVSS | | T.D. | STANDARD RIM Inch | S.W. mm | O.D. mm | MAX.LOAD KG | MAX.PRESSURE kPa | итав | SIDEWALL |
|-----|-------------|------|-----|------|----------------------|------------|------------|----------------|---------------------|----------|----------|
| | | | | | | | | | | | |
| 16 | 205/55ZRF16 | 94W | XL | 8.2 | 6 1/2J | 214 | 632 | 670 | 340 | 280/AA/A | BSW |
| 17 | 205/45ZRF17 | 88W | XL. | 8 | 7J | 206 | 616 | 560 | 340 | 280/AA/A | BSW |
| 17 | 205/50ZRF17 | 93W | XL | 8 | 6 1/2J | 214 | 638 | 650 | 340 | 280/AA/A | BSW |
| 17 | 225/45ZRF17 | 94W | XL | 8 | 7 1/2J | 225 | 634 | 670 | 340 | 280/AA/A | BSW |
| 17 | 225/50ZRF17 | 98W | XL | 8.2 | 7J | 233 | 658 | 750 | 340 | 280/AA/A | BSW |
| 17 | 225/55ZRF17 | 101W | XL | 8.2 | 7J | 233 | 680 | 825 | 340 | 280/AAVA | BSW |
| 18 | 225/40ZRF18 | 92W | XL | 8 | 8J | 230 | 637 | 630 | 340 | 280/AA/A | BSW |
| 18 | 255/35ZRF18 | 94Y | XL | 8 | 9J | 260 | 635 | 670 | 340 | 280/AA/A | BSW |
| 19 | 245/40ZRF19 | 98Y | XL | 8 | 8 1/2J | 248 | 679 | 750 | 340 | 280/AA/A | BSW |
| 19 | 275/35ZRF19 | 100Y | XL | 8 | 9 1/2J | 278 | 675 | 800 | 340 | 280/AA/A | BSW |
| | | | | | | | | | | | |

NSW 2164

