


REGIONAL

REGIONAL D1 (Y126)



Application



Drive wheel position for regional.
Suitable for multiple-purpose transport on good road surface.

Long Mileage Solution

- Optimize internal contour design to improve durability significantly.
- Deepened pattern depth compound combined with widened tread width to enhance expected mileage markedly.

Low Failure Solution

- Reinforcing blocks between the main pattern blocks to make the force more uniform and reasonable.
- Open shoulder design and tiny crosswise grooves to enhance good heat dissipation capacity.

Transport Efficiency Solution

- Multiple 3D sipes to provide excellent heat dissipation and drive stability.
- Professional block pattern design to bring a powerful traction.

Travel Comfort Solution

- Widened tread width to improve driving stability effectively , giving drivers a better sense of driving.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	295/60R22.5	TL	18	9.00	9.75	151/148M	149/146L	22.0	250	292	926	329	436
2	295/80R22.5	TL	18	9.00	8.25	152/149M	154/149L	22.0	245	298	1044	335	487
3	315/60R22.5	TL	20	9.75	9.00	153/150K	152/149L	22.0	270	313	950	352	447
4	315/70R22.5	TL	18	9.00	9.75	151/148M	154/150L	22.0	265	312	1014	351	469
5	315/80R22.5	TL	18	9.00	9.75	156/150K	154/150M	22.0	255	312	1082	351	500
6	315/80R22.5	TL	20	9.00	9.75	157/154L	158/156K	22.0	255	312	1082	351	500

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

