


**REGIONAL**

**REGIONAL S1  
(Y209)**



**Application**



Steer wheel position for regional.  
Suitable for multiple-purpose transport on good road surface.

**Long Mileage Solution**

- Optimized internal contour design to improve durability significantly.
- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

**Low Failure Solution**

- Specially designed pattern grooves can effectively protect against stone embed and avoid early damage.

**Transport Efficiency Solution**

- Four straight mian pattern grooves to provide excellent handling and high-speed performance.
- Zigzag retiform tiny grooves to enhance outstanding braking and driving performance.

**Travel Comfort Solution**

- Widened tread width to improve driving stability effectively , giving drivers a better sense of driving.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	11R22.5	TL	16	8.25	7.50	144/142L	-	17.5	220	279	1054	318	491
2	295/80R22.5	TL	18	9.00	8.25	140/138M	154/149L	17.0	240	298	1044	335	487
3	315/70R22.5	TL	18	9.00	9.75	151/148M	154/150L	14.5	256	312	1014	351	469
4	315/70R22.5	TL	20	9.00	9.75	156/150L	154/150M	14.5	256	312	1014	351	469
5	315/80R22.5	TL	18	9.00	9.75	156/150K	154/150M	16.5	260	312	1076	351	500
6	315/80R22.5	TL	20	9.00	9.75	157/154J	158/156K	16.5	260	312	1076	351	500

**BRISBANE**

28 Ashover Rd  
Rocklea  
QLD 4106

**MELBOURNE**

41 Paraweena Dr  
Truganina  
VIC 3029

**SYDNEY**

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

**PERTH**

8 Glassford Rd  
Kewdale  
WA 6105

