



SDNR 29

(TRA CODE:E-4 L-4) SUPER DIRT N ROCK

Tire, sizes ranging from 18.00-25 up to 36.00-51, will give the performance you require. The tire with heavy-duty nylon construction and proven super tough tread compound is superior for services in mining, constructions and water conservancy works. Its premium wide and deep tread reduces slippage and increase stability and traction. Longer tire life than E-3 tire.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		T/ @50km/h		L/ @10km/h	
							mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa
WIDE BASE TIRE														
23.5-25	12	Δ	Δ	53.5	2.12	19.50/2.5	620	24.4	1654	65.1	5300	175	8000	225
	16	Δ	Δ								6150	225	9500	300
	20	Δ	Δ								7300	300	10900	375
26.5-25	20	—	Δ	53.5	2.12	22.00/3.0	696	27.4	1737	68.4	8250	250	13200	350
	26	—	Δ								9500	325	15000	450
29.5-25	22	—	Δ	57.0	2.25	25.00/3.5	792	31.2	1890	74.4	10000	250	15000	325

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity					
		TT	TL	mm	inch		Overall Width		Overall Diameter		T/ @50km/h		L/ @10km/h			
							mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa		
28	—	Δ											11500	325	17500	425
34	—	Δ											—	—	20000	525
Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity					
		TT	TL	mm	inch		Overall Width		Overall Diameter		Transportation @50km/h					
							mm	inch	mm	inch	Load Kg	Inflation Kpa				
REGULAR BASE TIRE																
18.00-25	20	Δ	Δ	53.5	2.12	13.00/2.5	536	21.1	1661	65.4	6500	350				
	24	Δ	Δ								7300	425				
	28	Δ	Δ								8000	500				
	32	Δ	Δ								8750	575				
	36	Δ	Δ								9250	625				
18.00-33	28	—	Δ	53.5	2.12	13.00/2.5	528	20.8	1864	73.4	9250	500				
	32	—	Δ								10000	575				
	36	—	Δ								10600	625				
21.00-35	32	—	Δ	53.5	2.12	15.00/3.0	589	23.2	2042	80.4	12150	500				
	36	—	Δ								12850	550				
	40	—	Δ								13500	600				
	42	—	Δ								13800	625				
24.00-35	36	—	Δ	57.0	2.25	17.00/3.5	683	26.9	2159	85.0	15500	475				
	42	—	Δ								17000	575				
	48	—	Δ								18500	650				
24.00-49	42	—	Δ	57.0	2.25	17.00/3.5	686	27.0	2512	98.9	20600	575				
	48	—	Δ								21800	650				
27.00-49	42	—	Δ	63.5	2.50	19.50/4.0	787	31.0	2680	105.5	23000	500				
	48	—	Δ								25000	575				
30.00-51	46	—	Δ	69.5	2.74	22.00/4.5	886	34.9	2868	112.9	29000	500				
	52	—	Δ								30000	550				
36.00-51	50	—	Δ	81.5	3.22	26.00/5.0	988	38.9	3226	127.0	37500	450				
	58	—	Δ								41250	525				

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

