



SLG II 9

(TRA CODE:G-2、L-2、R-4)
SUPER LOADER GRADER II

Tires for earthmovers, graders, loaders and industrial tractors. The directional tread lugs provide good performance and excellent traction on loose ground, soft soil and sand with self-cleaning action.



TRA CODE G-2 SERIES

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Grader @40km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
REGULAR BASE TIRE												
13.00-24 TG	12	△	△	24.0	0.94	10.00VA	353	13.9	1285	50.6	2725	300
	14	△	△								3000	325
	16	△	△								3250	375
	18	△	—								3500	425
14.00-24 TG	12	△	△	25.5	1.00	10.00VA	381	15.0	1354	53.3	3075	250
	16	△	△								3650	350
	20	△	△								4200	450
16.00-24 TG	16	△	△	30.5	1.20	10.00VA	455	17.9	1491	58.7	4500	300

TRA CODE L-2 SERIES

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		G/@40km/h		L/@10km/h	
							mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa
WIDE BASE TIR														
10.5/80-18	10	—	△	20.0	0.79	9×18	269	10.6	904	35.6	1950	375	—	—
10.5-20	10	—	△	26.0	1.02	9×20	269	10.6	955	37.6	2070	375	—	—
	12	—	△								2240	425	—	—
12.5/80-18	12	—	△	22.0	0.87	11×18	325	12.8	991	39.0	2240	350	—	—
12.5-20	12	—	△	23.0	0.91	11×20	325	12.8	1039	40.9	2300	350	—	—
15.5-25	12	△	△	25.0	0.98	12.00/1.3	394	15.5	1272	50.1	2650	250	5600	400

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105





Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		G/@40km/h		L/ @10km/h	
							mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa
16	Δ	Δ									3225	350	6750	550
17.5-25	12	Δ	Δ	25.5	1.00	14.00/1.5	450	17.7	1344	52.9	2900	200	6150	350
14	Δ	Δ									3000	225	6700	400
16	Δ	Δ									3350	275	7300	475
18	Δ	Δ									3550	300	8000	550
20	Δ	Δ									3650	325	8250	575
20.5-25	12	Δ	Δ	28.5	1.12	17.00/2.0	493	19.4	1460	57.5	3550	175	6700	250
16	Δ	Δ									4000	225	8250	350
18	Δ	Δ									4250	250	9250	425
20	Δ	Δ									4500	275	9500	450
23.5-25	16	Δ	Δ	31.5	1.24	19.50/2.5	592	23.3	1600	63.0	4750	200	9500	300
18	Δ	Δ									5150	225	10600	350
20	Δ	Δ									5450	250	10900	375

TRA CODE R-4 SERIES

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Max @40km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
14.9-24	8	Δ	—	25.0	0.98	W12、W13	378	14.9	1241	48.86	2300	210
	12	—	Δ								2900	290
16.9-24	10	Δ	Δ	24.0	0.94	W15L	396	15.6	1290	50.8	2900	220
	12	Δ	Δ								3250	260
	16	Δ	Δ								3775	300
16.9-28	10	Δ	Δ	25.5	1.00	W15L、W14L	396	15.6	1359	53.5	3075	220
	12	Δ	Δ								3450	260
18.4-24	10	Δ	Δ	25.5	1.00	W15L、W16L	450	17.7	1359	53.5	3350	210
	12	Δ	Δ								3750	250
	16	Δ	Δ								4500	330

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105





Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Max @40km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
18.4-26	10	△	△	25.5	1.00	DW16A、W15L	457	18.0	1372	54.0	3550	210
	12	△	△								4000	250
	14	—	△								4400	290
	16	△	△								4800	330
LOW PROFILE TIRE												
17.5L-24	8	△	△	25.0	0.98	W15L	445	17.5	1240	48.8	2430	180
	10	△	△								2800	220
	12	△	△								3125	260
19.5L-24	8	—	△	25.0	0.98	W15L、W16L、DW16A	495	19.5	1314	51.74	2725	170
	10	—	△								3000	190
	12	—	△								3450	230
21L-24	10	—	△	29.0	1.14	W18L、DW18A	533	21.0	1378	54.24	3350	180
	12	—	△								3875	220
	16	—	△								4500	280

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

