



SMLS

32

(TRA CODE:E-4)SUPER MINING
LOGGER SERVICE

Tires for mining, earthmoving and logging services for short hauls. The specially designed extra deep tread for earthmovers allows longer life and superior traction.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Transportation @50km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
REGULAR BASE TIRE												
12.00-24NHS	16	△	—	35.0	1.38	8.50	335	13.2	1272	50.1	3250	450
	18	△	—								3450	500
	24	△	—								4000	650
12.00-25	16	△	—	35.0	1.38	8.50	310	12.2	1275	50.2	3250	450
14.00-24NHS	20	△	—	44.5	1.75	10.00W	404	15.9	1412	55.6	4625	475
	24	△	—								5150	575
	28	△	—								5600	650
14.00-25NHS	20	△	△	44.5	1.75	10.00	406	16.0	1412	55.6	4625	475
	24	△	△								5150	575

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

