



SR

1

(TRA CODE: C-1) SMOOTH ROLLER

For rollers' compacting roadbed and services on asphalt road surface. The wide and smooth riding tread allows much even pressure on road. Also the tread compound provides good resistance to oily chemicals.



Tyre Size	P. R.	Type		Tread Depth	Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL			Overall Width		Overall Diameter		Loader@10km/H	
						mm	inch	mm	inch	Load Kg	Inflation Kpa
8.5/90-15K	6	—	△	Smooth	5.50F	220	8.65	782	30.8	1800	350
7.50-15NHS	6	△	—	Smooth	6.5	215	8.46	785	30.91	1850	400
	10	△	—							2360	625
	12	△	—							2650	750
	14	△	—							2900	875
7.50-16	10	△	—	Smooth	5.50F	215	8.46	810	31.89	2520	655
9.00-20NHS	12	△	—	Smooth	7.0	261	10.3	1028	40.5	4000	625
	14	△	—							4375	725
	16	△	—							4750	825
11.00-20NHS	16	△	—	Smooth	8.0	293	11.5	1082	42.6	5450	725
	18	△	—							5800	825
23.1-26 NHS	10	—	△	Smooth	DW20A	587	23.1	1575	62.0	3860	140

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

