



SS L-4S 46

(TRA CODE:L-4S) SOOPER SCOOPER

A superior underground mining tire is used when maximum wide and extra-deep tread is imperative. This strong nylon construction tire with special tough wearing tread rubber provides increased resistance to cut and wear and an extended tire life in the most severe underground mining conditions. Its resistance to heat build-up is not good as L-3S. Suited for low speed and short haul operations.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
REGULAR BASE TIRE												
10.00-20NHS 12	Δ	—	30.5	1.20	8.00	279	11.0	1069	42.1	3875	550	
14	Δ	—								4250	650	
16	Δ	—								4600	750	
12.00-20NHS 16	Δ	Δ	33.5	1.32	8.50	315	12.4	1173	46.2	5450	675	
20	Δ	Δ								6350	875	
12.00-24NHS 16	Δ	—	33.5	1.32	8.50	345	13.6	1283	50.5	6150	675	
20	Δ	—								6900	825	
24	Δ	—								7600	975	
14.00-24NHS 16	Δ	Δ	45.5	1.80	10.00W	361	14.2	1359	53.5	7300	550	
20	Δ	Δ								8500	700	
24	Δ	Δ								9500	850	
28	Δ	—								10000	925	
32	Δ	—								10400	1000	
16.00-25	24	—	Δ	50.5	2.00	11.25/2.0	414	16.3	1486	58.5	10600	650
28	Δ	Δ								11500	750	
32	Δ	Δ								12300	850	
18.00-25	32	Δ	Δ	53.5	2.12	13.00/2.5	483	19.0	1666	65.6	15000	750
36	—	Δ								16000	850	

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
9.50-20	14	Δ	—	25.5	1.00	7.00	264	10.39	1049	41.29	3900	700
54/18-25	24	—	Δ	45.5	1.80	14.00	434	17.1	1359	53.5	8950	655
	28	—	Δ								9750	760
WIDE BASE TIRE												
17.5-25	16	Δ	Δ	45.5	1.80	14.00/1.5	434	17.1	1359	53.5	7300	475
	20	Δ	Δ								8250	575
20.5-25	16	Δ	Δ	48.0	1.90	17.00/2.0	493	19.4	1491	58.7	8250	350
	20	Δ	Δ								9500	450
	24	Δ	Δ								10300	525
	28	Δ	Δ								11500	625
26.5-25	32	—	Δ	54.0	2.12	22.00/3.0	698	27.5	1798	70.8	17000	550
65 SERIES LOW PROFILE TIRE												
35/65-33	30	—	Δ	57.0	2.25	28.00/3.5	853	33.6	2088	82.2	21800	450

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

