

## SS L-5S

## 48

### (TRA CODE:L-5S) SOOPER SCOOPER

Specially designed tire with extra deep tread for underground mining loaders. Compared with L-4S underground mining tire, the tread is much deeper and more superior in resistance to cut, wear and puncture and offer a longer tire life. Also reduce the hard work from frequent tire changing. But the heat-resistance is not good as L-4S. More suited for short haul and low speed operations.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
REGULAR BASE TIRE												
12.00-24NHS 16	Δ	—		50.5	2.00	8.50	345	13.6	1283	50.5	6150	675
20	Δ	—									6900	825
24	Δ	—									7600	975

#### BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

#### MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

#### SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

#### PERTH

8 Glassford Rd  
Kewdale  
WA 6105





Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
14.00-24NHS	16	△	△	63.5	2.50	10.00W	361	14.2	1359	53.5	7300	550
	20	△	△								8500	700
	24	△	△								9500	850
	28	△	—								10000	925
	32	△	—								10400	1000
16.00-25	24	—	△	71.0	2.80	11.25/2.0	414	16.3	1486	58.5	10600	650
	28	—	△								11500	750
18.00-25	16	△	△	78.5	3.10	13.00/2.5	483	19.0	1666	65.6	10000	375
	20	△	△								11500	475
	24	△	△								12500	550
	28	△	△								13600	650
	32	△	△								15000	750
	36	△	△								16000	850
21.00-25	28	△	△	87.0	3.43	15.00/3.0	630	24.8	1798	70.8	16500	575
	32	△	△								17500	650
	36	△	△								18600	725
66/24-25	24	—	△	78.5	3.10	21.00	569	22.4	1669	65.7	12600	480
75/30-25	26	—	△	97.5	3.84	25.00	790	31.1	1923	75.7	17700	415
	28	—	△								18550	450
	32	—	△								20200	515
WIDE BASE TIRE												
17.5-25	16	△	△	63.5	2.50	14.00/1.5	434	17.1	1359	53.5	7300	475
	20	△	△								8250	575
	24	—	△								9050	675
20.5-25	16	—	△	76.0	3.00	17.00/2.0	493	19.4	1491	58.7	8250	350
	20	—	△								9500	450

## BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

## MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

## SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

## PERTH

8 Glassford Rd  
Kewdale  
WA 6105





Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
							Overall Width		Overall Diameter		Loader@10km/h	
		TT	TL	mm	inch		mm	inch	mm	inch	Load Kg	Inflation Kpa
24	—	Δ									10300	525
28	—	Δ									11500	625
23.5-25	20	—	Δ	78.5	3.10	19.50/2.5	566	22.3	1669	65.7	10900	375
24	—	Δ									12500	475
28	—	Δ									13600	550
26.5-25	26	—	Δ	87.0	3.43	22.00/3.0	696	27.4	1801	70.9	15000	450
32	—	Δ									17000	550
36	—	Δ									18300	625
29.5-25	22	—	Δ	97.5	3.84	25.00/3.5	770	30.3	1923	75.7	15000	325
28	—	Δ									17500	425
29.5-29	28	—	Δ	97.5	3.84	25.00/3.5	770	30.3	2055	80.9	19000	425
34	—	Δ									21200	525
37.25-35	36	—	Δ	114.0	4.50	31.00/4.0	1006	39.6	2418	95.2	30750	450
42	—	Δ									33500	525
37.5-39	44	—	Δ	114.0	4.50	32.00/4.5	993	39.1	2588	101.9	37500	550
52	—	Δ									41300	650
65 SERIES LOW PROFILE TIRE												
35/65-33	24	—	Δ	97.5	3.84	28.00/3.5	853	33.6	2085	82.1	19000	350
30	—	Δ									21800	450
40/65-39	30	—	Δ	108.0	4.25	32.00/4.0	1001	39.4	2423	95.4	27250	375
36	—	Δ									30750	475
45/65-45	38	—	Δ	118.0	4.65	36.00/4.5	1102	43.4	2723	107.2	38750	425

## BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

## MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

## SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

## PERTH

8 Glassford Rd  
Kewdale  
WA 6105

