

## SXMH-HT 43

### (TRA CODE:L-5)SUPER EXTRA MINE HAULAGE HALF TRACK

Strong nylon construction with tread compound specially formulated for severe cutting and tearing conditions. The half-track tire is designed to perform on machines where a slick tread is preferred, when occasional traction is necessary. For excellent tire life, the SXMH-HT is designed for your machine.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
							Overall Width		Overall Diameter		Loader@10km/h	
		TT	TL	mm	inch		mm	inch	mm	inch	Load Kg	Inflation Kpa
59/23-25	40	—	Δ	50.5	2.00	19.50	559	22.0	1494	58.8	12100	690
WIDE BASE TIRE												
29.5-25	22	—	Δ	101.5	4.00	25.00/3.5	770	30.3	1923	75.7	15000	325
	28	—	Δ								17500	425
29.5-29	28	—	Δ	101.5	4.00	25.00/3.5	790	31.1	2055	80.9	19000	425
	34	—	Δ								21200	525
37.25-35	36	—	Δ	114.0	4.50	31.00/4.0	930	36.6	2418	95.2	30750	450
	42	—	Δ								33500	525
37.5-39	36	—	Δ	114.0	4.50	32.00/4.5	993	39.1	2588	101.9	33500	450
	44	—	Δ								37500	550
	52	—	Δ								41300	650
65 SERIES LOW PROFILE TIRE												
35/65-33	24	—	Δ	101.5	4.00	28.00/3.5	853	33.6	2088	82.2	19000	350
	30	—	Δ								21800	450
40/65-39	30	—	Δ	108.0	4.25	32.00/4.0	1001	39.4	2423	95.4	27250	375
	36	—	Δ								30750	475
45/65-45	38	—	Δ	118.0	4.65	36.00/4.5	1102	43.4	2723	107.2	38750	425

#### BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

#### MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

#### SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

#### PERTH

8 Glassford Rd  
Kewdale  
WA 6105

