



## SXMH L-5 42

(TRA CODE:L-5)

### SUPER EXTRA MINE HAULAGE

Specially designed deep tread of half-slick and heavy lugs combined with special compound for severe cut resistance provide excellent resistance to tear, puncture, cut and abrasion. But the traction and heat resistance are not as good as DNR(Z) III. More suited for the services where non-big traction required and in quite low speed working conditions. It can provide a longer life than regular E-3/L-3 tread design under severe working conditions, like: power construction with lots of rocks, above or underground mines, quarry, waste and slags and garbage disposal field. Much longer tire life than regular E-3/L-3 tires



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity		
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h		
							mm	inch	mm	inch	Load Kg	Inflation Kpa	
REGULAR BASE TIRE													
21.00-25	28	—	Δ	76.0	3.00	15.00/3.0	617	24.3	1796	70.7	16500	575	
	32	—	Δ								17500	650	
	36	—	Δ								18600	725	
WIDE BASE TIRE													
26.5-25	20	Δ	Δ	89.0	3.50	22.00/3.0	696	27.4	1801	70.9	13200	350	
	26	Δ	Δ								15000	450	
	32	Δ	Δ								17000	550	
29.5-25	22	—	Δ	101.5	4.00	25.00/3.5	770	30.3	1923	75.7	15000	325	
	28	—	Δ								17500	425	
29.5-29	22	—	Δ	101.5	4.00	25.00/3.5	790	31.1	2055	80.9	16000	325	
	28	—	Δ								19000	425	
	34	—	Δ								21200	525	
	40	—	Δ								23600	625	
33.25-35	32	—	Δ	98.5	3.88	27.00/3.5	884	34.8	2367	93.2	25750	450	
	38	—	Δ								28000	525	
33.5-33	32	—	Δ	106.0	4.18	28.00/4.0	851	33.5	2261	89.0	25750	425	

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
	38	—	△								29000	525
37.25-35	36	—	△	114.0	4.50	31.00/4.0	930	36.6	2418	95.2	30750	450
	42	—	△								33500	525
37.5-39	44	—	△	114.0	4.50	32.00/4.5	993	39.1	2588	101.9	37500	550
	52	—	△								41300	650
	58	—	△								44000	725
65 SERIES LOW PROFILE TIRE												
35/65-33	24	—	△	101.5	4.00	28.00/3.5	853	33.6	2088	82.2	19000	350
	30	—	△								21800	450
	32	—	△								22400	475
40/65-39	30	—	△	108.0	4.25	32.00/4.0	1001	39.4	2423	95.4	27250	375
	36	—	△								30750	475
45/65-45	38	—	△	118.0	4.65	36.00/4.5	1102	43.4	2723	107.2	38750	425

### BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

### MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

### SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

### PERTH

8 Glassford Rd  
Kewdale  
WA 6105

