



TG:01™

DESIGNED FOR FITMENT OF DRIVE AXLE OF VEHICLES USED IN CONSTRUCTION SITE, FEATURES HIGH RETREADABILITY AND DELIVERS RESISTANCE TO LACERATION, HIGH TRACTION ON ROUGH TERRAINS AND MUD, MILEAGE AND ACOUSTIC COMFORT ON ASPHALTED ROAD.



- Increased tread width promotes **mileage**
- Tread blocks geometry (Pirelli patent) optimized to ease **self-cleaning**, thus ensuring better **traction** and **even wear**
- Protection elements (Pirelli patent) at the bottom of grooves avoid stone trapping enhancing tyre **resistance**
- Directional tread pattern for better **traction**, **acoustic comfort** and even wear



Also for use on front axles
(all wheel drive vehicles)

SIZE	LOAD INDEX/SPEED CODE	MARKINGS	EFFICIENCY LABELS		
9.00R20 TT	140/137 K	M+S			
10.00R20 TT	146/143 K	M+S			
11.00R20 TT	151/142 K	M+S			
11R22.5 TL	149/146 K	M+S			
12R22.5 TL	152/148 K	M+S			
13R22.5 TL	156/150 K	3PMSF M+S	D	A	75 dB
295/80R22.5 TL	152/148 L	3PMSF M+S	E	A	76 dB
315/80R22.5 TL	156/150 K	3PMSF M+S	E	B	74 dB

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

