

# HT

# TRAVIA H/T

### Long Mileage Solution

- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

### Transport Efficiency Solution

- Professional shoulder block to enhance excellent riding stability at high speed.



### Noise Reduction Solution

- Wide groove compound combined with corrugated steel disc to enhance expected mileage markedly.

NO.	Series	Size	SL /XL	Sidewall Type	PR	Rim	Load Index	Speed Rating	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max. Air Pressure (KPa)	Max. Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	55"	215/55R18	SL	OWL	-	7.0	95	H	690	1521	350	51	9.4	226	693
2		215/55R18	XL	OWL	-	7.0	99	V	775	1709	340	50	9.4	226	693
3		215/60R17	SL	OWL	-	6.5	96	H	710	1565	350	51	9.4	221	690
4	60"	235/60R18	SL	OWL	-	7.0	103	H	875	1929	350	51	9.4	240	739
5		235/60R18	SL	OWL	-	7.0	103	V	875	1929	350	51	9.4	240	739
6	65"	235/65R17	SL	OWL	-	7.0	104	T	900	1984	350	51	9.4	240	738
7		245/65R17	SL	OWL	-	7.0	107	T	975	2149	350	51	9.8	248	750
8		265/65R17	SL	OWL	-	8.0	112	H	1120	2469	350	51	9.8	272	776
9		215/70R16	SL	OWL	-	6.5	100	H	800	1764	350	51	9.4	221	708
10	70"	225/70R16	SL	OWL	-	6.5	103	T	875	1929	350	51	9.4	228	722
11		235/70R16	SL	OWL	-	7.0	106	T	950	2094	350	51	9.4	240	736
12		245/70R16	SL	OWL	-	7.0	107	T	975	2149	350	51	9.8	248	750
13		265/70R16	SL	OWL	-	8.0	112	T	1120	2469	350	51	9.8	272	778
14		265/70R17	SL	OWL	-	8.0	115	T	1215	2679	350	51	9.8	272	804
15		LT265/70R17	-	BSW	10	8.0	121/118	R	1450/1320	3195/2910	550	80	11.3	272	804
16		LT285/70R17	-	BSW	8	8.5	121/118	S	1450/1320	3195/2910	450	65	11.3	292	832
17	75"	235/75R15	XL	OWL	-	6.5	109	T	1030	2271	340	50	9.4	235	733
18		265/75R16	SL	OWL	-	7.5	116	T	1250	2756	350	51	9.8	267	804
19		LT215/75R15	-	OWL	8	6.0	106/103	R	950/875	2095/1930	450	65	11.3	216	703
20		LT225/75R16	-	BSW	10	6.0	115/112	R	1215/1120	2680/2470	550	80	11.3	223	744
21	LT235/75R15	-	OWL	10	6.5	116/113	S	1250/1150	2755/2535	550	80	11.3	235	733	
22	LT245/75R16	-	BSW	10	7.0	120/116	R	1400/1250	3085/2755	550	80	11.3	248	774	
23	LT245/75R17	-	BSW	10	7.0	121/118	R	1450/1320	3195/2910	550	80	11.3	248	800	
24	LT265/75R16	-	BSW	6	8.5	109	R	1030	2270	350	50	11.3	268	775	
25	31X10.50R15LT	-	BSW	10	7.5	123/120	R	1550/1400	3415/3085	550	80	11.3	267	804	
26	80"	LT235/80R17	-	BSW	10	6.5	120/117	R	1400/1285	3085/2835	550	80	11.3	235	808
27	85"	LT235/85R16	-	BSW	10	6.5	120/116	R	1400/1250	3085/2755	550	80	11.3	235	806

### BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

### MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

### SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

### PERTH

8 Glassford Rd  
Kewdale  
WA 6105

