

MT

TRAVIA M/T

Long Mileage Solution

- High abrasion tread compound to enhance expected mileage markedly.

Low Failure Solution

- Specially designed shoulder curve can effectively protect against overwear and avoid early damage.



High Load Solution

- Reinforced tyre body and band structure to provide stronger load capacity.

| NO. | Series | Size | SL /XL | Sidewall Type | PR | Rim | Load Index | Speed Rating | Max. Load Capacity (KG) | Max. Load Capacity (LBS) | Max. Air Pressure (KPa) | Max. Air Pressure (PSI) | Tread Depth (mm) | Section Width (mm) | Overall Diameter (mm) |
|-----|--------|---------------|--------|---------------|----|------|------------|--------------|-------------------------|--------------------------|-------------------------|-------------------------|------------------|--------------------|-----------------------|
| 1 | 50" | 33X12.50R20LT | - | OWL | 10 | 10.0 | 114 | Q | 1180 | 2600 | 450 | 65 | 15.0 | 318 | 826 |
| 2 | 60" | 33X12.50R18LT | - | OWL | 10 | 10.0 | 118 | Q | 1320 | 2910 | 450 | 65 | 15.0 | 318 | 826 |
| 3 | | 35X12.50R20LT | - | OWL | 10 | 10.0 | 121 | Q | 1450 | 3195 | 450 | 65 | 15.0 | 318 | 877 |
| 4 | 70" | LT285/70R17 | - | OWL | 10 | 8.5 | 121/118 | Q | 1450/1320 | 3195/2910 | 550 | 80 | 15.0 | 292 | 832 |
| 5 | | LT265/70R17 | - | OWL | 10 | 8.0 | 121/118 | Q | 1450/1320 | 3195/2910 | 550 | 80 | 15.0 | 272 | 804 |
| 6 | 75" | LT245/75R16 | - | OWL | 10 | 7.0 | 120/116 | Q | 1400/1250 | 3085/2755 | 550 | 80 | 15.0 | 248 | 774 |
| 7 | | LT265/75R16 | - | OWL | 10 | 7.5 | 123/120 | Q | 1550/1400 | 3415/3085 | 550 | 80 | 15.0 | 267 | 804 |
| 8 | | LT285/75R16 | - | OWL | 10 | 8.0 | 126/123 | Q | 1700/1550 | 3750/3415 | 550 | 80 | 15.0 | 268 | 834 |
| 9 | | 31X10.50R15LT | - | OWL | 6 | 8.5 | 109 | Q | 1030 | 2270 | 350 | 50 | 15.0 | 265 | 775 |

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

