

VAN

TRAVIA VAN

Long Mileage Solution

- High abrasion tread compound to enhance expected mileage markedly.

All-weather Grip Solution

- Three straight mian pattern grooves to enhance outstanding wet grip.



High Load Solution

- Reinforced tyre body and band structure to provide stronger load capacity.

NO.	Series	Size	SL /XL	Sidewall Type	PR	Rim	Load Index	Speed Rating	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max. Air Pressure (KPa)	Max. Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	60"	215/60R16C	-	BSW	8	6.5	103/101	T	875/825	1929/1819	375	54	9.7	221	664
2		175/65R14C	-	BSW	6	5.0	90/88	T	600/560	1323/1235	375	54	9.7	177	584
3		205/65R16C	-	BSW	8	6.0	107/105	T	975/925	2149/2039	475	69	9.7	209	672
4	65"	215/65R16C	-	BSW	8	6.5	109/107	R	1030/975	2271/2149	475	69	9.7	221	686
5		225/65R16C	-	BSW	8	6.5	112/110	R	1120/1060	2469/2337	475	69	9.7	228	698
6		235/65R16C	-	BSW	8	7.0	115/113	R	1215/1150	2679/2535	475	69	9.7	240	712
7		165/70R13C	-	BSW	6	5.0	88/86	R	560/530	1235/1168	375	54	9.7	170	562
8		165/70R14C	-	BSW	6	5.0	89/87	R	580/545	1279/1201	375	54	9.7	170	588
9		175/70R14C	-	BSW	6	5.0	95/93	R	690/650	1521/1433	375	54	9.7	177	602
10	70"	195/70R15C	-	BSW	8	6.0	104/102	R	900/850	1984/1874	450	65	9.7	201	655
11		205/70R15C	-	BSW	8	6.0	106/104	R	950/900	2094/1984	450	65	9.7	209	669
12		215/70R15C	-	BSW	8	6.5	109/107	R	1030/975	2271/2149	450	65	9.7	221	683
13		225/70R15C	-	BSW	8	6.5	112/110	R	1120/1060	2469/2337	450	65	9.7	228	697
14		185/75R16C	-	BSW	8	5.0	104/102	R	900/850	1984/1874	475	69	9.7	184	684
15	75"	195/75R16C	-	BSW	8	5.5	107/105	R	975/925	2149/2039	475	69	9.7	196	698
16		205/75R16C	-	BSW	8	5.5	110/108	R	1060/1000	2337/2205	475	69	9.7	203	714
17		215/75R16C	-	BSW	8	6.0	113/111	R	1150/1090	2535/2403	475	69	9.7	216	728
18		155R12C	-	BSW	8	4.5	88/86	Q	560/530	1235/1168	450	65	9.7	157	550
19		155R13C	-	BSW	6	4.5	85/83	Q	515/487	1135/1074	350	50	9.7	157	578
20		165R13C	-	BSW	6	4.5	91/89	Q	615/580	1356/1279	350	50	9.7	167	596
21		185R14C	-	BSW	8	5.5	102/100	Q	850/800	1874/1764	450	65	9.7	188	650
22	80"	195R14C	-	BSW	8	5.5	106/104	Q	950/900	2094/1984	450	65	9.7	198	666
23		195R15C	-	BSW	8	5.5	106/104	Q	950/900	2094/1984	450	65	9.7	196	693
24		205R14C	-	BSW	8	6.0	109/107	Q	1030/975	2271/2149	450	65	9.7	208	686
25		205R14C	-	WSW	8	6.0	109/107	Q	1030/975	2271/2149	450	65	9.7	208	686
26		205R16C	-	BSW	8	6.0	110/108	Q	1060/1000	2337/2205	450	65	9.7	208	736
27		205R16C	-	WSW	8	6.0	110/108	Q	1060/1000	2337/2205	450	65	9.7	208	736

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

