


URBAN

**URBAN G1
(Y999)**



Application



General wheel position for urban road. Suitable for passenger transport on urban road surface.

Long Mileage Solution

- Optimize internal contour design to improve durability significantly.
- High abrasion tread compound combined with deepened groove depth to enhance expected mileage markedly.

Low Failure Solution

- Reinforced sidewall design to avoid external injury during urban transport.
- Specially designed pattern grooves can effectively protect against stone embed and avoid early damage.

Transport Efficiency Solution

- Multiple 3D sipes to provide excellent heat dissipation and drive stability.
- Optimize tread contour design is especially suitable for frequent swerve and brake.

Fleet Management Solution

- General position design is easy for regular switch and fleet management.
- Reinforced chafer and professional bead to significantly improve body strength and retread capacity.



M+S

NO.	Size	Type	PR	Standard Rim	Permitted Rim	L/SS	Second L/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	11R22.5	16	18	8.25	7.50	148/145J	151/148F	21.5	235	279	1054	318	491
2	275/70R22.5	18	18	8.25	9.00	148/145J	152/148F	21.5	240	276	958	311	446

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

