

REGIONAL

Y103 (DD13)

Application



Drive wheel position for regional.
Suitable for multiple-purpose transport
on good road surface.

Long Mileage Solution

- Optimize internal contour design to improve durability significantly.
- Excellent belt durability to sharply increase mileage.

Low Failure Solution

- Special base rubber formula to reduce internal heat and avoid early damage of tread and shoulder.
- Excellent footprint distributing weight-bearing forces evenly over a large area and ensure uniform wear.

All-weather Grip Solution

- Widened tread width to enhance outstanding wet grip.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	11R22.5	TL	14	8.25	7.50	144/142L	-	24.0	213	279	1065	318	491
2	11R22.5	TL	16	8.25	7.50	146/143L	-	24.0	213	279	1065	318	491
3	11R24.5	TL	14	8.25	7.50	146/143L	-	24.0	213	279	1116	318	516
4	11R24.5	TL	16	8.25	7.50	149/146L	-	24.0	213	279	1116	318	516
5	285/75R24.5	TL	14	8.25	-	144/141L	-	24.0	213	283	1056	318	493
6	295/75R22.5	TL	14	9.00	8.25	144/141L	-	24.0	213	297	1020	335	474

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

