


REGIONAL

Y105 (DD15)



Application



Drive wheel position for regional.
Suitable for multiple-purpose transport on good road surface.

Long Mileage Solution

- Optimize internal contour design to improve durability significantly.
- Deepened pattern depth compound combined with widened tread width to enhance expected mileage markedly.

Low Failure Solution

- Excellent footprint distributing weight-bearing forces evenly over a large area to ensure uniform wear.
- Open shoulder design and tiny crosswise grooves to enhance good heat dissipation capacity.

Transport Efficiency Solution

- Multiple tiny sipes to provide excellent heat dissipation and reduces rolling noise.
- Professional block pattern design to bring a powerful traction.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	11R22.5	TL	16	8.25	7.50	160J	-	20.5	219	279	1065	318	491
2	13R22.5	TL	18	9.75	9.00	154/151K	-	20.5	250	320	1136	350	521
3	295/80R22.5	TL	18	9.00	8.25	152/149M	154/149L	21.0	245	298	1044	335	487
4	315/70R22.5	TL	18	9.00	9.75	156/150L	154/150L	19.0	258	312	1020	351	469
5	315/70R22.5	TL	20	9.00	9.75	157/154L	154/150M	19.0	258	312	1020	351	469
6	315/80R22.5	TL	18	9.00	9.75	156/150L	154/150M	20.5	243	312	1082	351	500
7	315/80R22.5	TL	20	9.00	9.75	157/154L	-	20.5	243	312	1082	351	500

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

