


LONG HAUL

Y201 (DA20)



Application



Steer wheel position for long haul.
Suitable for long-distance transport
on excellent road surface.

Long Mileage Solution

- Outstanding belt durability to sharply increase mileage.
- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

Low Failure Solution

- Special shoulder grooves and sipes to avoid early damage of shoulder.
- Excellent footprint distributing weight-bearing forces evenly over a large area to ensure uniform wear.

Transport Efficiency Solution

- Specially designed zigzag pattern groove bottom to provide extra traction.
- Four straight mian pattern grooves provides excellent handling and high-speed performance.

All-weather Grip Solution

- Multiple tiny sipes to provide excellent heat dissipation and wet grip.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	11R22.5	TL	14	8.25	7.50	144/142M	-	15.0	220	279	1054	318	491
2	11R22.5	TL	16	8.25	7.50	146/143M	-	15.0	220	279	1054	318	491
3	11R24.5	TL	14	8.25	7.50	146/143L	-	15.0	220	279	1104	318	516
4	11R24.5	TL	16	8.25	7.50	149/146L	-	15.0	220	279	1104	318	516
5	225/70R19.5	TL	12	6.75	6.00	125/123M	-	13.0	176	226	811	254	382
6	225/70R19.5	TL	14	6.75	6.00	128/126M	-	13.0	176	226	811	254	382
7	245/70R19.5	TL	16	7.50	6.75	135/133L	-	13.0	195	248	839	279	391
8	265/70R19.5	TL	16	7.50	8.25	140/138M	-	13.0	200	262	867	295	402
9	285/75R24.5	TL	14	8.25	-	144/141M	-	15.0	220	283	1050	318	493
10	295/60R22.5	TL	18	9.00	9.75	150/147K	149/146L	16.0	242	292	926	329	436
11	295/75R22.5	TL	14	9.00	8.25	144/141M	-	15.0	225	297	1014	335	474
12	295/80R22.5	TL	18	9.00	8.25	152/149M	154/149L	15.0	240	298	1044	335	487
13	295/80R22.5	TL	18	9.00	8.25	152/149M	154/149L	15.0	240	298	1044	335	487
14	315/60R22.5	TL	20	9.75	9.00	153/150K	152/149L	14.5	264	313	945	352	447
15	315/70R22.5	TL	18	9.00	9.75	151/148M	154/150L	14.5	240	312	1014	351	469
16	315/70R22.5	TL	20	9.00	9.75	156/150L	154/150M	14.5	240	312	1014	351	469
17	315/80R22.5	TL	18	9.00	9.75	156/150L	154/150M	16.0	245	312	1076	351	500
18	315/80R22.5	TL	20	9.00	9.75	157/154L	-	16.0	245	312	1076	351	500

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

