


ON/OFF ROAD

Y205 (DA25)
Y205+



Application



General wheel position for on/off road.
Suitable for multiple-purpose transport
on multiple road surface.

Long Mileage Solution

- Optimize internal contour design to improve durability significantly.
- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

Low Failure Solution

- Specialty designed pattern grooves can effectively protect against stone embed and avoid early damage.

Transport Efficiency Solution

- Three zigzag mian pattern grooves to provide excellent traction and brake performance.

All-weather Grip Solution

- Zigzag tiny pattern groovess to provide excellent heat dissipation and wet grip.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	L/SS	Second L/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	11R22.5	TL	16	8.25	7.50	146/143L	-	17.5	220	279	1054	318	491
2	12.00R24	TT	20	8.50	8.50V,9.0	160/157K	-	16.0	237	315	1226	372	572
3	13R22.5	TL	18	9.75	9.00	154/151K	-	18.0	245	320	1124	350	521
4	295/80R22.5	TL	18	9.00	8.25	152/149M	154/149L	17.0	240	298	1044	335	487
5	315/80R22.5	TL	18	9.00	9.75	156/150L	154/150M	18.0	244	312	1076	351	500
6	315/80R22.5	TL	20	9.00	9.75	157/154L	-	18.0	244	312	1076	351	500
7	11R22.5*	TL	16	8.25	7.50	146/143L	-	17.5	220	279	1054	318	491

Remark : 1. This pattern is also could use as steer tyre which suitable for inter-city bus on good road surface.
2. This size with "*" means "Y205+".

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

