

REGIONAL

Y211 (DA21)

Application



General wheel position for regional.
Suitable for multiple purposes transport on good road surface.

Long Mileage Solution

- Outstanding belt durability to sharply increase mileage.
- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

Low Failure Solution

- Excellent footprint distributing weight-bearing forces evenly over a large area to ensure uniform wear.

Transport Efficiency Solution

- Multiple tiny sipes to provide excellent heat dissipation and reduces rolling noise.
- Four zigzag sipes pattern grooves to provide excellent handling and high-speed performance.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	10R22.5	TL	16	7.50	6.75	144/142M	-	15.0	195	254	1019	290	476
2	9R22.5	TL	14	6.75	6.00,7.50	144/142M	-	14.5	176	229	974	261	457

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

