


LONG HAUL

Y219 (DT29)



Application



Trailer wheel position for long haul.
Suitable for long-distance transport
on excellent road surface.

Long Mileage Solution

- High saturation pattern design to provide outstanding durability.
- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

Low Failure Solution

- Special shoulder curve design to ensure uniform wear.
- Half-open shoulder design and tiny crosswise grooves to enhance good heat dissipation capacity.

Transport Efficiency Solution

- Five straight mian pattern grooves to provide excellent handling and high-speed performance.

Travel Comfort Solution

- Widened tread width to improve driving stability effectively , giving drivers a better sense of driving.



M+S

NO.	Size	Type	PR	Standard Rim	Permitted Rim	L/SS	Second L/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	385/55R22.5	TL	20	12.25	11.75	160K	158L	18.0	312	386	996	-	466
2	385/65R22.5	TL	20	11.75	12.25	160K	158L	18.0	298	389	1072	-	494
3	385/65R22.5	TL	22	11.75	12.25	162J	-	18.0	298	389	1072	-	494

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

