


ON/OFF ROAD

Y501 (DD51)



Application



Drive wheel position for on/off road. Suitable for multiple-purpose transport on multiple road surface.

Long Mileage Solution

- Deepened pattern depth to effectively prolong service life.

Low Failure Solution

- Specially designed pattern grooves can effectively protect against stone embed and avoid early damage.
- Stepped shoulder design to enhance good heat dissipation capacity.

Transport Efficiency Solution

- Wide transverse groove to provide excellent traction and brake performance.

All-weather Grip Solution

- Multiple tiny sipes to provide excellent heat dissipation and wet grip.



M+S



| NO. | Size | Type | PR | Standard Rim | Permitted Rim | LI/SS | Second LI/SS | Tread Depth (mm) | Tread Width (mm) | Section Width (mm) | Overall Diameter (mm) | Static Loaded Radius(mm) | Min.distance between rim centers(mm) |
|-----|-------------|------|----|--------------|---------------|----------|--------------|------------------|------------------|--------------------|-----------------------|--------------------------|--------------------------------------|
| 1 | 12.00R24 | TL | 20 | 8.5 | 8.50V,9.0 | 160/157K | - | 19.0 | 242 | 315 | 1238 | 372 | 572 |
| 2 | 225/70R19.5 | TL | 14 | 6.75 | 6.00 | 128/126L | - | 15.0 | 177 | 226 | 817 | 254 | 382 |
| 3 | 245/70R19.5 | TL | 14 | 7.50 | 6.75 | 133/131L | - | 15.0 | 194 | 248 | 845 | 279 | 391 |
| 4 | 265/70R19.5 | TL | 16 | 7.50 | 8.25 | 140/138M | - | 17.5 | 214 | 262 | 867 | 295 | 402 |
| 5 | 315/80R22.5 | TL | 18 | 9.00 | 9.75 | 156/150K | 154/150L | 18.5 | 254 | 312 | 1082 | 351 | 500 |
| 6 | 315/80R22.5 | TL | 20 | 9.00 | 9.75 | 157/154L | 158/156K | 18.5 | 254 | 312 | 1082 | 351 | 500 |

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

