

ON/OFF ROAD

Y516

Application



Drive wheel position for on/off road.
Suitable for multiple-purpose transport
on multiple road surface.

Long Mileage Solution

- Deepened pattern depth to effectively prolong service life.
- Specially tread compound to protect pattern bolcks from falling apart.

Low Failure Solution

- Specially designed pattern grooves can effectively protect against stone embed and avoid early damage.
- Half-opean shoulder design to enhance good heat dissipation capacity and uniform wear.

Transport Efficiency Solution

- Wide transverse groove to provide excellent traction and brake performance.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	12.00R24	TL	20	8.5	8.50V,9.0	160/157K	-	20.0	242	315	1238	372	572
2	315/80R22.5	TL	18	9.00	9.75	156/150K	154/150L	19.0	254	312	1082	351	500
3	315/80R22.5	TL	20	9.00	9.75	157/154L	-	19.0	254	312	1082	351	500

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

