


**ON/OFF ROAD**

**Y529**



**Application**



Drive wheel position for on/off road.  
Suitable for multiple-purpose transport  
on multiple road surface.

**Long Mileage Solution**

- Deepened pattern depth to effectively prolong service life.

**Low Failure Solution**

- Specially designed pattern grooves can effectively protect against stone embed and avoid early damage.
- Open shoulder design to enhance good heat dissipation capacity.

**Transport Efficiency Solution**

- Wide transverse groove to provide excellent traction and brake performance.

**Energy Efficiency Solution**

- Directional pattern design to reduce rolling noise.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	315/80R22.5	TL	18	9.00	9.75	156/150K	154/150L	24.5	255	312	1082	351	500
2	315/80R22.5	TL	20	9.00	9.75	157/154J	158/156G	24.5	255	312	1082	351	500

**BRISBANE**

28 Ashover Rd  
Rocklea  
QLD 4106

**MELBOURNE**

41 Paraweena Dr  
Truganina  
VIC 3029

**SYDNEY**

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

**PERTH**

8 Glassford Rd  
Kewdale  
WA 6105

