

Application



General wheel position for regional.
Suitable for multiple-purpose transport
on good road surface.

Long Mileage Solution

- Optimize internal contour design to improve durability significantly.
- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

Low Failure Solution

- Special base rubber formula to reduce internal heat and avoid early damage of tread and shoulder.

Transport Efficiency Solution

- Four zigzag mian pattern grooves to provide excellent excellent traction and braking performance.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	11.00R20	TT	18	8.0	-	154/151K	-	16.5	223	293	1085	-	-
2	12.00R20	TT	18	8.5	-	168L	-	17.5	240	315	1125	-	-

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

