

**ON/OFF ROAD**

**Y631 (DM63)**

**Application**



Trailer wheel position for on/off road. Suitable for multiple-purpose transport on multiple road surface.

**Long Mileage Solution**

- Deepened pattern depth to effectively prolong service life.
- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

**Low Failure Solution**

- Specially designed pattern grooves can effectively to protect against stone embed and avoid early damage.
- Open shoulder design to enhance good heat dissipation capacity.

**Transport Efficiency Solution**

- Hybrid pattern design to provide excellent traction and brake performance.
- Three zigzag mian pattern grooves to provide excellent handling performance.

**All-weather Grip Solution**

- Multiple tiny sipes to provide excellent heat dissipation and wet grip.



**E4 M+S**

NO.	Size	Type	PR	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	385/65R22.5	TL	20	11.75	12.25	160K	158L	18.0	298	389	1072	-	494
2	385/65R22.5	TL	22	11.75	12.25	162J	-	18.0	298	389	1072	-	494
3	425/65R22.5	TL	20	13.00	11.75,13.00	165K	-	18.0	320	422	1124	-	515

**BRISBANE**

28 Ashover Rd  
Rocklea  
QLD 4106

**MELBOURNE**

41 Paraweena Dr  
Truganina  
VIC 3029

**SYDNEY**

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

**PERTH**

8 Glassford Rd  
Kewdale  
WA 6105

