

ON/OFF ROAD

Y866 (DD86)

Y866+

Application



Drive wheel position for on/off road.
Suitable for multiple-purpose transport
on multiple road surface.

Long Mileage Solution

- Deepened pattern depth to effectively prolong service life.
- Specially tread compound combined with reinforced block to enhance expected mileage markedly.

Low Failure Solution

- Specially designed pattern grooves can effectively protect against stone embed and avoid early damage.
- Big main blocks compound combined with reinforced block to enhance puncture resistance and cut resistance.
- Open shoulder design to enhance good heat dissipation capacity and uniform wear.



NO.	Size	Type	PR	Standard Rim	Permitted Rim	L/SS	Second L/SS	Tread Depth (mm)	Tread Width (mm)	Section Width (mm)	Overall Diameter (mm)	Static Loaded Radius(mm)	Min.distance between rim centers(mm)
1	7.50R16LT	TT	14	6.00G	5.50F,6.50H	122/118K	-	16.0	170	215	815	255	375
2	8.25R16LT	TT	16	6.50H	6.00G,6.5	128/124K	-	16.0	180	235	865	278	397
3	10.00R20*	TT	18	7.5	7.50V,8.0	149/146K	-	19.0	216	278	1065	328	486
4	11.00R20*	TT	18	8.0	8.00V,8.5	152/149K	-	20.0	230	293	1096	346	499
5	12.00R20*	TT	18	8.5	8.50V,9.0	154/151K	-	20.5	242	315	1136	372	516

Remark : This size with "*" means "Y866+".

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

