



JY520

Features:

- > Super single tyre for trailer axle with an excellent driving stability
- > An outstanding wear resistance and durability
- > Improved compound for a reduction of heat build-up




JY501

Features:

- > All position pattern designed for med and long-haul and bus service
- > Stone-release grooves prevent stone-sticking
- > Improved wear resistance tread compound conquer heat build-up
- > An outstanding high speed performance and stable road contact
- > Serration groove walls also provide a fairly good traction

The technological parameter of each tyre size

Tyre size	PR	LI/SS	Type	Standard rim	Overall Diameter		Section Width		Tread depth		Load				Pressure			
					mm	inch	mm	inch	mm	inch (32")	S(kg)	D(kg)	S(lbs.)	D(lbs.)	S(kPa)	D(kPa)	S(psi)	D(psi)
385/65R22.5	20	158/L (160/K)	T/L	11.75	1072	42.2	389	15.3	16	20	4500		9920		900		130	
425/65R22.5	20	165/K	T/L	12.25	1124	44.3	422	16.6	16	20	5150		11400		830		120	




Recommended Vehicle Types & Position

● Recommended ○ Optional ✘ Not suitable

The technological parameter of each tyre size

Tyre size	PR	LI/SS	Type	Standard rim	Overall Diameter		Section Width		Tread depth		Load				Pressure			
					mm	inch	mm	inch	mm	inch (32")	S(kg)	D(kg)	S(lbs.)	D(lbs.)	S(kPa)	D(kPa)	S(psi)	D(psi)
7.50R20	14	130/125K	T/T	6.00	935	36.8	215	8.5	13	16	1885	1655	4150	3665	840	770	120	110
10.00R20	16	146/143L	T/T	7.50	1054	41.5	278	10.9	15	19	3000	2725	6610	6010	830	830	120	120
10.00R20	18	149/146K	T/T	7.50	1054	41.5	278	10.9	15	19	3250	3000	7165	6610	930	930	135	135
11R22.5	14	144/142M	T/L	8.25	1054	41.5	279	11.0	15	19	2800	2650	6175	5840	720	720	105	105
11R22.5	16	148/145M	T/L	8.25	1054	41.5	279	11.0	15	19	3150	2900	6945	6395	840	840	120	120
11R24.5	14	146/143L	T/L	8.25	1104	43.5	279	11.0	15	19	3000	2725	6610	6005	720	720	105	105
11R24.5	16	149/146L	T/L	8.25	1104	43.5	279	11.0	15	19	3190	3045	7160	6610	850	850	123	123



Recommended Vehicle Types & Position

● Recommended ○ Optional ✘ Not suitable