



JY601



- Cool running
- High durability

Size	Standard Rim	Pr	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			kg		lbs		kpa		psi		S	D			D	B
			S	D	S	D	S	D	S	D	S	D				
7.00R16	5.50F	12	1215	1060	2680	2340	670	670	97	97	115	110	11.5	L	775	205
7.00R16	5.50F	14	1320	1180	2910	2600	770	770	110	110	118	114	11.5	L	775	205
7.50R16	6.00G	12	1400	1250	3085	2755	670	670	97	97	120	116	12.5	K	805	215
7.50R16	6.00G	14	1500	1320	3310	2910	770	770	110	110	122	118	12.5	L	805	215
8.25R16	6.50H	14	1700	1500	3750	3310	670	670	97	97	126	122	12.5	L	855	235
8.25R16	6.50H	16	1800	1600	3970	3530	770	770	110	110	128	124	12.5	L	855	235
8.25R20	6.5	16	2430	2300	5360	5070	930	930	135	135	139	137	13.5	K	974	236
9.00R20	7.0	14	2575	2430	5680	5360	790	790	115	115	141	139	15	K	1019	259
9.00R20	7.0	16	2800	2650	6170	5840	900	900	130	130	144	142	15	K	1019	259
10.00R20	7.5	16	3000	2725	6610	6010	830	830	120	120	146	143	16	K	1054	278
10.00R20	7.5	18	3250	3000	7165	6610	930	930	135	135	149	146	16	K	1054	278
11.00R20	8.0	16	3350	3075	7385	6780	830	830	120	120	150	147	16.5	K	1085	293
11.00R20	8.0	18	3550	3250	7830	7170	930	930	135	135	152	149	16.5	K	1085	293
12.00R20	8.5	18	3750	3450	8270	7610	830	830	120	120	154	151	17	K	1125	315
12.00R20	8.5	20	4000	3650	8820	8050	900	900	130	130	156	153	17	K	1125	315
11R22.5	8.25	14	2800	2650	6175	5840	720	720	105	105	144	142	16	M	1054	279
11R22.5	8.25	16	3150	2900	6945	6395	840	840	120	120	148	145	16	M	1054	279
11R24.5	8.25	14	3000	2725	6610	6005	720	720	105	105	146	143	16	L	1104	279
11R24.5	8.25	16	3250	3000	7160	6610	830	830	120	120	149	146	16	M	1104	279
12R22.5	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	16.5	L	1085	300
12R22.5	9.00	18	3550	3150	7825	6945	850	850	125	125	152	148	16.5	K	1085	300
13R22.5	9.75	18	3750	3350	8270	7390	850	850	125	125	154	150	16	L	1124	320
13R22.5	9.75	20	4000	3350	8820	7390	900	900	130	130	156	150	16	J	1124	320
295/80R22.5	9.00	16	3550	3150	7825	6945	850	850	125	125	152	149	17.5	M	1050	298
295/80R22.5	9.00	18	3550	3250	7825	7165	900	900	130	130	152	149	17.5	L	1050	298
315/80R22.5	9.00	16	3450	3150	7605	6945	760	760	110	110	151	148	16	L	1076	312
315/80R22.5	9.00	18	3750	3450	8270	7610	830	830	120	120	154	151	16	L	1076	312
315/80R22.5	9.00	20	4000	3650	8820	8045	850	850	125	125	156	153	16	K	1076	312

1mm=0.039inch

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

