

# ROADX

## HP H03



### ■ Safety

Four main tread grooves improve safety by providing excellent handling, firm grip, and efficient water drainage.



### ■ Tread Compound

The tread compound formulation makes the tread more adhesive for better grip on both dry and wet roads.

### ■ Fuel Efficient

The tire is composed of a silica compound that will reduce rolling resistance for better fuel economy.

RIM	SIZE	LI/SS		T.D.	STANDARD RIM	S.W.	O.D.	MAX. LOAD	MAX. PRESSURE	SIDEWALL
				mm	inch	mm	mm	KG	kPa	
12	155/70R12	73T	--	7	4.50B	157	523	365	300	RWL
12	165/70R12	77T	--	7	5.00B	170	537	412	300	RWL
13	215/50R13	84H	--	7	7.00B	226	545	495	300	RWL
15	175/50R15	75H	--	7.5	5 1/2J	182	557	387	300	BSW
16	195/40R16	80V	XL	7	7J	200	562	450	340	BSW
16	205/35R16	79V	XL	7	7 1/2J	212	550	437	340	BSW
16	205/40ZR16	83W	XL	7	7 1/2J	212	570	487	340	BSW
16	215/40ZR16	86W	XL	7	7 1/2J	218	578	530	340	BSW
16	225/35ZR16	85Y	XL	7	8J	230	564	515	340	BSW
17	195/40ZR17	81W	XL	7	7J	200	588	462	340	BSW
17	205/35ZR17	80W	XL	7	7 1/2J	212	575	450	340	BSW

1inch=25.4mm 1kPa=0.142psi 1KG=2.2 lbs XL Extra Load LI Load Index SS Speed Symbol

### BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

### MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

### SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

### PERTH

8 Glassford Rd  
Kewdale  
WA 6105

