


ROADX



**LTC
C01**



Optimized wet and dry performance, improved wear resistance, and longer tread life.

Pattern Grooves ■

Wide S-shaped grooves efficiently drain water and decrease stone retention.



■ Wear Resistance

Optimized tread pattern design ensures even contact pressure for better wear resistance.



RIM	SIZE	LI/SS	T.D.	STANDARD RIM	S.W.	O.D.	MAX.LOAD	MAX.PRESSURE	SIDEWALL
			mm	inch	mm	mm	KG	kPa	
15	6.50R15LT	10PR 106/101N	10	5.50F	185	730	950/825	560	BSW
15	7.00R15LT	10PR 109/105L	10	5.50F	200	750	1030/925	560	BSW
15	7.00R15LT	10PR 109/105N	10	5.50F	200	750	1030/925	560	BSW
16	6.50R16LT	10PR 107/102N	10.5	5.50F	185	750	975/850	560	BSW
16	7.00R16LT	12PR 115/110N	10.5	5.50F	200	775	1215/1060	670	BSW

1inch=25.4mm | 1kPa=0.142psi | 1KG=2.2 lbs | XL Extra Load | LI Load Index | SS Speed Symbol

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

