

ROADX

SUV-MT


M/T




TRAVERSABLE CROSS-COUNTRY HIGH DURABILITY PUNCTURE RESISTANT RESILIENT




Staggered shoulder blocks improve traction and climbing capability.



+



Uses a specialized rubber compound to create a more balanced tire with strong grip.



■ Grooves

Deepened grooves allow mud to easily be discharged from the tread at both high and low speeds. The design also offers better grip when traveling on rocky or rugged roads.



■ Shoulder Design

Large blocks on the shoulder vastly enhance handling on muddy and rock roads.



■ Safety

The shield pattern which extends from the sidewall protects the sidewall from abrasions and increase traction on mud roads. The carcass is designed with three layers of polyester fabric to make it rugged and resistant to strong impacts.

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105



| RIM | SIZE | | LI/SS | T.D. | STANDARD RIM | S.W. | O.D. | MAX.LOAD | MAX.PRESSURE | SIDEWALL |
|-----|---------------|------|----------|------|--------------|------|------|-----------|--------------|----------|
| | | | | mm | inch | mm | mm | KG | kPa | |
| 15 | 30x9.50R15LT | 6PR | 104Q | 15.3 | 7 1/2J | 240 | 756 | 900 | 350 | OWL |
| 15 | 31x10.50R15LT | 6PR | 109Q | 15.3 | 8 1/2J | 268 | 781 | 1030 | 350 | OWL |
| 15 | 33x12.50R15LT | 6PR | 108Q | 15.3 | 10J | 318 | 832 | 1000 | 250 | OWL |
| 15 | 35x12.50R15LT | 6PR | 113Q | 15.3 | 10J | 318 | 883 | 1150 | 250 | OWL |
| 15 | LT235/75R15 | 6PR | 104/101Q | 15.3 | 6 1/2J | 235 | 739 | 900/825 | 350 | OWL |
| 16 | LT235/85R16 | 10PR | 120/116Q | 15.3 | 6 1/2J | 235 | 812 | 1380/1260 | 550 | OWL |
| 16 | LT245/75R16 | 10PR | 120/116Q | 15.3 | 7J | 248 | 780 | 1380/1260 | 550 | OWL |
| 16 | LT265/75R16 | 8PR | 119/116Q | 15.3 | 7 1/2J | 267 | 810 | 1360/1250 | 450 | OWL |
| 16 | LT265/75R16 | 10PR | 123/120Q | 15.3 | 7 1/2J | 267 | 810 | 1550/1400 | 550 | OWL |
| 17 | 33x12.50R17LT | 8PR | 114Q | 16.3 | 10J | 318 | 832 | 1180 | 350 | OWL |
| 17 | 35x12.50R17LT | 10PR | 121Q | 16.3 | 10J | 318 | 883 | 1450 | 450 | OWL |
| 17 | LT265/70R17 | 10PR | 121/118Q | 15.5 | 8J | 272 | 810 | 1450/1320 | 550 | OWL |
| 17 | LT285/70R17 | 10PR | 121/118Q | 15.5 | 8 1/2J | 292 | 838 | 1450/1320 | 550 | OWL |
| 18 | 33x12.50R18LT | 10PR | 118Q | 16.3 | 10J | 318 | 832 | 1320 | 450 | BSW |
| 18 | 35x12.50R18LT | 10PR | 123K | 16.7 | 10J | 318 | 883 | 1550 | 450 | BSW |
| 18 | 35x12.50R18LT | 10PR | 123Q | 16.7 | 10J | 318 | 883 | 1550 | 450 | BSW |
| 20 | 33x12.50R20LT | 10PR | 114Q | 16.3 | 10J | 318 | 832 | 1180 | 450 | BSW |
| 20 | 35x12.50R20LT | 10PR | 121Q | 16.3 | 10J | 318 | 883 | 1450 | 450 | BSW |
| 20 | LT305/55R20 | 10PR | 121/118Q | 16.3 | 9 1/2J | 316 | 850 | 1450/1320 | 450 | BSW |

| | | | | | |
|--------------------------|---------------|-------------|---------------|---------------|-----------------|
| 1inch=25.4mm | 1kPa=0.142psi | 1KG=2.2 lbs | XL Extra Load | LI Load Index | SS Speed Symbol |
| OWL Outline White Letter | | | | | |

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

